PERFORMANCE MADE SMARTER

Communication enabler

4511

– Programming display for system 4000 and 9000 devices
– Modbus RTU protocol interface over RS-485
– Monitor process value from the built-in display
– High 2.5 kV isolation to host unit
– Shielded RJ45 connector on top

Application

- The 4511 detachable display adds Modbus RTU RS-485 serial communications to all current and future 4000/9000 units.
- The unit converts a wide array of sensors and analog device signals measured by the system 4000 like uni- and bipolar mA and voltage signals, potentiometer, Lin. R, RTD and TC, to a Modbus communication line signal.
- When mounted on a system 9000 device any signal coming from or going to I.S. classified area, like AI, AO, DI and DO signals, can be converted to a Modbus network.
- All individual unit operating parameters can easily and quickly be configured by using the Modbus communication or by using the front display menu.
- The easily readable 4511 display can be used to read the process signal, simulate the output signal, indicate sensor errors and internal device errors.

Technical characteristics

- 4511 has full 4501 functionality for unit programming, process signal monitoring and diagnostics handling.
- Modbus RTU protocol is supported using a serial RS-485 communication wiring.
- Multidrop half-duplex connection via shielded RJ45 connector.
- High safe galvanic isolation of 2.5 kVAC between the serial wiring and the connected system 4000/9000 units.
- Modbus parameters such as address, baud rate, stop bit(s), and parity bit are configured from the 4511 display, which also stores parameters.

Mounting / installation / programming

- Mounting in Zone 2 / Div 2.
- The 4511 can be moved from one device to another. The individual system 4000/9000 unit configuration of the first device can be saved and downloaded to subsequent devices.
- Programmed parameters can be protected by a userdefined password.
- When mounted on devices that are installed upside down, a menu item allows the display on the 4511 to be rotated 180° and the up/down buttons to switch function.

Applications



Up to 32 devices per segment without the use of a network repeater

This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order:

Type
4511

Environmental Conditions

Operating temperature	-20°C to +60°C
Storage temperature	-20°C to +85°C
Relative humidity	< 95% RH (non-cond.)
Protection degree	IP20
Installation in	Pollution degree 2 & meas. / overvoltage cat. II

Mechanical specifications

Dimensions (HxWxD)	73.2 x 23.3 x 26.5 mm
Dimensions (HxWxD) w/ 4000/9000 unit	109 x 23.5 x 131 mm
Weight approx	30 g
Connection	RJ45 - shielded

Common specifications

Supply

Max. required power	≤ 0.15 W

Isolation voltage

Isolation voltage, test / working	2.5 kVAC / 250 VAC reinforced isolation

Response time

Response time	< 20 ms
Signal / noise ratio	> 60 dB
Update rate	> 50 Hz
Extended EMC immunity: NAMUR NE21, A criterion, burst	No loss of communication
Signal type	RS-485 half duplex
Serial protocol	Modbus RTU
Modbus mode	RTU - slave
Devices on an RS485 line	Up to 32 (w/o a repeater)
Data rates, baud	2400, 4800, 9600, 19200, 38400, 57600, 115200
Automatic baudrate detection	Yes - can be configured ON or OFF
Parity	Even, Odd, None
Stop bit(s)	1 or 2
Digital addressing	1...247
Response delay	0...1000 ms

Observed authority requirements

EMC	2014/30/EU
LVD	2014/35/EU
EAC	TR-CU 020/2011

Approvals

DNV Marine	Stand. f. Certific. No. 2.4
ATEX	DEKRA 13ATEX0098 X
IECEx	DEK 13.0026 X
FM	0003049132-C
UL	UL 61010-1